



TECHNICAL DATA SHEET



Clinox **ECO** X2



Clinox **PRO** X2



Clinox **AIR** X2



Clinox **POWER** X2



Clinox **SURFACE** X2

TDS_X2LINE_2022_04-R00

| | | | | | |
|-----------------------|----------------------------------|---|---|---|---|
| Mains Voltage | 230 V - 50/60 Hz | 230 V - 50/60 Hz | 230 V - 50/60 Hz | 230 V - 50/60 Hz | 230 V - 50/60 Hz |
| Maximum primary power | 1200 VA | 1800 VA | 1200 VA | 1800 VA | 2400 VA |
| Output current | 0÷30 A | 0÷30 A | 0÷30 A | 0÷50 A | 0÷100 A |
| Output voltage | 3÷30 V AC/DC | 3÷30 V AC/DC | 3÷30 V AC/DC | 3÷30 V AC/DC | 3÷30 V AC/DC |
| Output power | 900 W | 900 W | 900 W | 1500 W | 2400 W |
| Voltage regulation | 3÷30 V (step 1 V) | 3÷30 V (step 1 V) | 3÷30 V (step 1 V) | 3÷30 V (step 1 V) | 3÷30 V (step 1 V) |
| Current regulation | 1 fixed position: 30 A | 2 Positions: Low: 15 A High: 30 A | 2 Positions: Low: 15 A High: 30 A | 3 Positions: Low: 15 A Mid: 30 A High: 50 A | 3 Positions: Low: 30 A Mid: 50 A High: 100 A |
| Tank capacity | - | 1,8 l | 1,8 l | 1,8 l | 1,8 l |
| Dispensing rate | - | 1÷3,6 l/h | 1÷3,6 l/h | 1÷3,6 l/h | 1÷3,6 l/h |
| Pump regulation | - | Dynamic Manual | Dynamic Manual | Dynamic Manual | Dynamic Manual |
| | - | Automatic: 8 levels | Automatic: 8 levels | Automatic: 8 levels | Automatic: 8 levels |
| Weight | 6,8 kg | 18 kg | 16,5 kg | 16,5 kg | 18,5 kg |
| Dimensions l/b/h | 410 x 170 x 238 mm | 543 x 228 x 315 mm | 543 x 228 x 315 mm | 543 x 228 x 315 mm | 543 x 228 x 315 mm |
| Torches | - | Suction torch - L. 3 m Small manual torch* D&W torch* Marking torch* | Blowing torch - L. 4 m Small manual torch* D&W torch* Marking torch* | Blowing torch - L. 4 m Small manual torch* D&W torch* Marking torch* | Blowing torch - L. 6 m Small manual torch* D&W torch* Marking torch* |
| Functions | Cleaning Polishing Marking | Cleaning Polishing Marking | Cleaning Polishing Marking | Cleaning Polishing Marking | Cleaning Polishing Marking |